

State of California
AIR RESOURCES BOARD

EXECUTIVE ORDER A-86-196
Relating to Certification of New Motor Vehicles

MITSUBISHI MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That 1996 model-year Mitsubishi Motors Corporation exhaust emission control systems are certified as described below for passenger cars:

Fuel Type: Gasoline

Engine Family: TMT3.0V8GFEK Displacement: 3.0 Liters (181.4 Cubic Inches)

Exhaust Emission Control Systems and Special Features:

Exhaust Gas Recirculation
Dual Heated Oxygen Sensors (two)
Dual Warm Up Three-Way Catalytic Converters
Three Way Catalytic Converter
Sequential Multiport Fuel Injection

Vehicle models, transmissions, engine codes and evaporative emission control families are listed on attachments.

The certification exhaust emission standards (in-use compliance standards in parentheses) for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.25 (0.32)	3.4 (5.2)	0.4 (0.4)	10.0 (10.0)
100,000	0.31 (n/a)	4.2 (n/a)	0.6 (n/a)	n/a

The certification exhaust emission values for this engine family in grams per mile are:

<u>Miles</u>	<u>Non-Methane Hydrocarbons</u>	<u>Carbon Monoxide</u>	<u>Nitrogen Oxides</u>	<u>Carbon Monoxide (20°F)</u>
50,000	0.14	1.7	0.1	5.2
100,000	0.17	2.0	0.1	n/a

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the aforementioned exhaust emission standards based on its submitted plan to comply with the fleet average non-methane organic gas (NMOG) exhaust mass emission requirements as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That under the submitted NMOG fleet average compliance plan, if the manufacturer incurs a NMOG debit for the aforementioned model year based on the projected NMOG fleet average exceeding the value required by the above-referenced standards and test procedures, all incurred NMOG debits by the manufacturer shall be equalized as required by the standards and test procedures.

BE IT FURTHER RESOLVED: That, based on a separate compliance plan submitted by the vehicle manufacturer, the listed vehicle models are permitted alternative in-use compliance as set forth in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".

BE IT FURTHER RESOLVED: That the submitted alternative in-use compliance plan satisfies the requirement that a maximum of 20 percent of the manufacturer's projected sales of 1996 model-year California-certified passenger cars and light-duty trucks will be subject to alternative in-use compliance as stipulated in the above-referenced standards and test procedures.

BE IT FURTHER RESOLVED: That the vehicle manufacturer is certifying the listed vehicle models to the 50,000-mile evaporative emission standards applicable to 1980 through 1994 model-year vehicles in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles", and the listed vehicle models comply with those standards.

BE IT FURTHER RESOLVED: That, based on the evaporative emission phase-in compliance schedule submitted by the vehicle manufacturer, the listed vehicle models shall not be subject to the running loss and useful life standards set forth in the "California Evaporative Emission Standards and Test Procedures for 1978 and Subsequent Model Motor Vehicles."

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the "California Motor Vehicle Emission Control Label Specifications" for the aforementioned model year (Title 13, California Code of Regulations, Section 1965).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's "Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks" for the aforementioned model year (Title 13, California Code of Regulations, Section 2235).

BE IT FURTHER RESOLVED: That the listed vehicle models also comply with the Board's high-altitude requirements and highway emission standards, and with the California Inspection and Maintenance emission standards in place at the time of certification, as stipulated in "California Exhaust Emission Standards and Test Procedures for 1988 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles".


BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.1) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicles, the manufacturer has submitted and the Executive Officer hereby approves the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

Vehicles certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachment.

Executed at El Monte, California this 30th day of August 1995.


R. B. Summerfield
Assistant Division Chief
Mobile Source Division

17-16.02

E.O. # A-96-96

Page 1 of 1

1996 MODEL-YEAR AIR RESOURCES BOARD SUPPLEMENTAL DATA SHEET
PASSENGER CARS, LIGHT-DUTY TRUCKS AND MEDIUM DUTY VEHICLES

Manufacturer: Mitsubishi Motors Corp Exh Engine Family: TMT3.0V8GFEK(2, CB-S)
Evap Engine Family: TMT1054AYMAD(Diamond) & TMT1058BYMAD(Stealth)
All Engine Codes in Eng Fam: CA 49S 50S_X AB 965
Exh Std: CA Tier-1 X TLEV LEV ULEV ZE ; US EPA Tier-1 X
Evap Std: 50K_X Useful Life with R/L In-Use Std: Full In-Use Alt In-Use_X
Veh Class(es): PC_X LDT1 LDT2 MGV1 MDV2 MDV3 MDV4 MDV5
Single Cert Std for Multi-Class Eng Fam: N/A (specify: N/A, LDT1, MDV1, ..., MDV4)
Fuel Type(s): Dedicated_X Flex-Fuel Dual-Fuel Bi-Fuel Gasoline_X
Diesel CNG LNG LPG M85 Other (specify) _____
Emis Test Fuel: \$ Indo_X Ph2 CNG LPG M85 Other (specify) _____
Diesel: 13 CCR 2282 40CFR 86.113-90 40CFR 86.113-94
Service Accum: Std AMA Mod AMA Mfr ADP Other (specify) AMA4 (Sec 20.07)
NMOG Test Proc: N/A_X Std Equiv R/L Test Proc: SHED Pt Source
Hybrid: Type A B C, APU Cycle (e.g., Otto, Diesel, Turbine) _____
Engine Configuration: V6 Displacement: 3.0 Liters / 181.4 Cubic Inches
Valves per Cylinder: 2 Rated HP: 161@5500RPM(Stealth), 172@5500RPM(Diamond)
Engine: Front X Mid Rear Drive: FWD_X RWD 4WD-FT 4WD-PT
Exhaust ECS (eg., EGR, MPI, TC, CAC): EGR+2HO2S(2)+2WWTWC+TWC+SPF
(abbreviations per SAE J1930 SEP91)

Engine Code (also list CAL/FED/BOTH)	Vehicle Models (if coded see attachment)	Trans. Type *1	ETW	DPA or RLBP	Ignition (ECM/PCM) Part No.	EGR System Part No.	Catalytic Converter Part No.
ABM(BOTH)	Dodge Stealth	M5	3500	7.0	Distributor: MD320732 (T5T43071)	EGR Valve: MD199283 (K5T58980)	Front(R): MR127572
BM(BOTH)				6.4			Front(L): MR126693
ABA(BOTH)		L4	3625	6.9	ECM: MD319637 (E2T61374)	Solenoid: MD161746 (K5T49681)	Rear: MB906265 (K4)
BA(BOTH)				6.3			
ABA-J(BOTH)	Mitsubishi Diamante	L4	3875	7.5	Distributor: MD320732 (T5T43071) ECM: MD319634 (E2T61273)	EGR Valve: MD153340 (K5T56471) Solenoid: MD161746 (K5T49681)	Front(R): MR127572 Front(L): MR126693 Rear: MB925699 (Q2) or XR266347

*1: M-Manual transmission
L-Automatic transmission with lock-up

Revisions: 06-21-95, 07-13-95, ~~08-29-95~~ \$
17.16.02-11